



MOSS

AREAS OF APPLICATION


Shops • Cafes • Restaurants • Offices • Training Halls • Hospitals • Factories • Facility
Suitable for use in the areas requiring long-lasting and high lumen lighting.



MOSS

4"


RECESSED LED DOWNLIGHT LUMINAIRE




PRODUCT SPECIFICATIONS

Body	: Aluminum Body and Circle / RAL9003
Optic Cover	: PMMA and PS Opal Diffuser
Driver	: Osram-Tridonic-Philips-3N
Led Chip	: Samsung, Osram, Seoul
Input Voltage	: 220-240V/AC 50-60Hz
Temperature Range	: -10°C~+40°C
CRI	: CRI > 80
IP Class	: IP40
Options	: Application Options : Recessed/Surface Mounted Color Temperature: 3000K/4000K/6500K Emergency Kit - DALI


PHOTOMETRIC DISTRIBUTION



TECHNICAL DRAWING



PLASTER CEILING HOLE SIZE



PRODUCT SPECIFICATIONS

Item Code	Power (W)	Luminaire Lumen (lm)	Color Temperature (K)	Efficiency (lm/W)	Dimensions (LxWxH)	Cut Size (Ø)	Qty/Carton	Carton Size (LxWxH)	G.W/Carton
LDL10.009	9W	900	3000/4000/6500	100lm/W	130x45mm	110mm	20	270x270x270mm	6 kg
LDL10.012	12W	1.200	3000/4000/6500	100lm/W	130x45mm	110mm	20	270x270x270mm	6 kg

*3N Company has the right to make any changes it deems necessary without prior notice.
*Technical data has a tolerance of ±10%.