



COOL


APPLICATION AREAS

Shops • Cafes • Restaurants • Offices • Training Halls • Hospitals • Facilities • Sports Facilities
It is ideal for use in areas that demand lights with high lumen and long lifespan.



COOL

LINEAR LUMINAIRE (DISCOUNT STORE)




PRODUCT SPECIFICATIONS


- Body** : Alu Body / RAL9005
- Optic Cover** : PC Opal Diffuser
- Led Driver** : Osram-Tridonic-Philips-3N
- Led Chip** : Samsung, Osram, Seoul
- Input Voltage** : 220-240V/AC 50-60Hz
- Temperature Range** : -10°C~+40°C
- CRI** : CRI > 80
- IP Class** : IP40
- Options** : Body Color Options : RAL9016/RAL7001
Application Options : Surface/Pendant
Color Temperature : 3000K/4000K/6500K
Emergency Kit - DALI



PHOTOMETRIC DISTRIBUTION




TECHNICAL DRAWING



ACCESSORIES

Joining Connector



Surface Mounting Kit



U-Shape Mounting Kit



End Cap



Energy Input



1,2M. Suspension Wire



PRODUCT SPECIFICATIONS

Item Code	Power (W)	Luminaire Lumen (lm)	Color Temperature (K)	Efficiency (lm/W)	Dimensions (LxWxH)	Qty/Carton	Carton Size (LxWxH)	G.W/Carton
LLN30.036	36W	3.600	3000/4000/6500	100lm/W	1000x55x65mm	6	1545x170x250mm	8.2 kg

*3N Company has the right to make any changes it deems necessary without prior notice.
*Technical data has a tolerance of ± 10%.