



# JUDAS

## APPLICATION AREAS

Shops • Cafes • Restaurants • Offices • Training Halls • Hospitals • Facilities • Sports Facilities  
It is ideal for use in areas that demand lights with high lumen and long lifespan.




# JUDAS

LINEAR LUMINAIRE (DISCOUNT STORE)



Including edge strips color options to complement your corporate branding




## PRODUCT SPECIFICATIONS


- Body** : Alu Body / RAL9005
- Optic Cover** : PC Opal Diffuser
- Led Driver** : Osram-Tridonic-Philips-3N
- Led Chip** : Samsung, Osram, Seoul
- Input Voltage** : 220-240V/AC 50-60Hz
- Temperature Range** : -10°C~+40°C
- CRI** : CRI > 80
- IP Class** : IP40
- Options** : Body Color Options : RAL9016/RAL7001  
Application Options : Surface/Pendant  
Color Temperature : 3000K/4000K/6500K  
Emergency Kit - DALI

It manufactures in 15 cm modular and extendable up to 3 mt.

### PHOTOMETRIC DISTRIBUTION



### TECHNICAL DRAWING



### ACCESSORIES

<b>Joining Connector</b>  SP060.10.00001	<b>Surface Mounting Kit</b>  R070.10.00091	<b>U-Shape Mounting Kit</b>  SP060.10.00003
<b>End Cap</b>  R010.40.00028	<b>Energy Input</b>  R050.10.00002	<b>1,2M. Suspension Wire</b>  C030.98.12001

### PRODUCT SPECIFICATIONS

Item Code	Power (W)	Luminaire Lumen (lm)	Color Temperature (K)	Efficiency (lm/W)	Dimensions (LxWxH)	Qty/Carton	Carton Size (LxWxH)	G.W/Carton
LLN20.036	36W	3.600	3000/4000/6500	100lm/W	1000x57x87mm	6	1545x170x250mm	7.56 kg

\*3N Company has the right to make any changes it deems necessary without prior notice.  
\*Technical data has a tolerance of ± 10%.