

## AREAS OF APPLICATION

Shops • Cafes • Restaurants • Offices • Training Halls • Hospitals Suitable for use in the areas requiring decorative and high lumen lighting.





## **LED BAR ALUMIUM BODY**

OPTIONAL

MAGNETIC LED BAR

LED BATTEN LIGHT



Body	: Alu Body / PC Cover				
Optic Cover	: Opal PC Difuser				
Led Chip	: Osram-Samsung-Seoul				
Input Voltage	: 220-240V/AC 50-60Hz				
Temperature Range : -20°C~+40°C					
CRI	: CRI > 80				
IP Class	: IP40				
Options	: Color Temperature : 3200K/4000K/6500K Red/Green/Blue/Amber/Meat				

Including magnet that sticks on metal perfectly. Optional Magnetic Led Bar Light





PHOTOMETRIC DISTRIBUTION 180° Gamma Angles 120° 105 90° 80 75° 160 60° 240


Including magnet that

sticks on metal perfectly. **Optional Magnetic** 

Led Bar Light

0

TECHNICAL DRAWING





FIXTURE ACCESSORIES



## 105 90° 75 60° 45° 45° 320 400 30 15° 0° 15° 30° 180.0 0.0 η:100.00% 270.0 90.0

Item Code	Power (W)	Luminaire Lumen (lm)	Color Temperature (K)	Efficiency (lm/W)	Dimensions (LxWxH)	Qty/Carton	Carton Size (LxWxH)	G.W/Carton		
LLN12.014	14W	1.050	3000/4000/6500	75lm/W	1000x22x18mm	-	-	-		
Nucleon sector bande a bande a bande a bande a bande a bande a										

<sup>\*</sup>3N Company has the right to make any changes it deems necessary without prior notice. \*Technical data has a tolerance of ± 10%.

PRODUCT SPECIFICATIONS