

LED BAR

AREAS OF APPLICATION

 $\textbf{Shops} \bullet \textbf{Cafes} \bullet \textbf{Restaurants} \bullet \textbf{Offices} \bullet \textbf{Training Halls} \bullet \textbf{Hospitals}$ Suitable for use in the areas requiring decorative and high lumen lighting.



























LED BAR FOOD SECTION

LED BATTEN LIGHT





PHOTOMETRIC DISTRIBUTION 105° 105° 90° 75° 60° 160 60° 240 45° 320 45° 45° 320 75° 180.0 0.0 \$\Pi:100.00%\$

PRODUCT SPECIFICATIONS

Body : PC Body / PC Cover

Optic Cover : Opal PC Difuser

Led Chip : Osram-Samsung-Seoul

Input Voltage : 220-240V/AC 50-60Hz

Temperature Range: -20°C~+40°C

CRI : CRI > 80


IP Class : IP40

Options : Color Temperature:


Red/Green/Blue/Amber/Meat

Including magnet that sticks on metal perfectly.

Optional Magnetic Led Bar Light




It manufactures in 5 cm modular and extendable up to 3 mt.




1lt manufactures in 10 cm modular and extendable up to 3 mt.

FIXTURE ACCESSORIES

Hanging Kits







	Н
⊢	—

PRODUCT SPECIFICATIONS

Item Code	Power (W)	Luminaire Lumen (lm)	Color Temperature	Efficiency (lm/W)	Dimensions (LxWxH)	Qty/Carton	Carton Size (LxWxH)	G.W/Carton
LLN12.014	14W	-	Meat/Fish/Bakery/Fresh	-	1000x22x18mm	-	-	-

^{*3}N Company has the right to make any changes it deems necessary without prior notice.

^{*}Technical data has a tolerance of ± 10%.