




# VIOLET

## AREAS OF APPLICATION

Shop • Cafes • Restaurants • Parking Lots • Offices • Training Halls • Hospital • Factory • Facility  
Designed to use in the areas requiring long-lasting and high lumen lighting.




# VIOLET 30x60




## PRODUCT SPECIFICATIONS

- Body** : Dkp Steel Sheet / RAL9003
- Optic Cover** : PMMA Opal Diffuser
- Driver** : Osram-Tridonic-Philips-3N
- Led Chip** : Samsung, Osram, Seoul
- Input Voltage** : 220-240V/AC 50-60Hz
- Temperature Range** : -10°C~+40°C
- CRI** : CRI > 80
- IP Class** : IP40
- Options** : Application Options :  
Plaster Ceiling/Suspended Ceiling/  
Clip In Mounted/Surface Mounted  
Color Temperature : 3000K/4000K/6500K  
Emergency Kit - DALI

PHOTOMETRIC DISTRIBUTION




TECHNICAL DRAWING



ACCESSORY FOR PLASTER CEILING



PLASTER CEILING HOLE SIZE



## PRODUCT SPECIFICATIONS

Item Code	Power (W)	Luminaire Lumen (lm)	Color Temperature (K)	Efficiency (lm/W)	Dimensions (LxWxH)	Qty/Carton	Carton Size (LxWxH)	G.W/Carton
LOF20.021 / Plaster	21W	2.100	3000/4000/6500	100lm/W	295x595x60mm	10	620x340x450mm	19.4 kg
LOF20.021 / Stonewool	21W	2.100	3000/4000/6500	100lm/W	295x595x60mm	10	620x340x450mm	19.4 kg
LOF20.021 / Surface M.	21W	2.100	3000/4000/6500	100lm/W	300x600x60mm	10	620x340x450mm	19.4 kg
LOF20.021 / Clip In	21W	2.100	3000/4000/6500	100lm/W	300x600x60mm	10	620x340x450mm	19.4 kg

\*3N Company has the right to make any changes it deems necessary without prior notice.  
\*Technical data has a tolerance of ± 10%.